



EXPLECO GLASS POOL SAND

INSTALLATION INSTRUCTIONS

IF YOU HAVEN'T READ THESE INSTRUCTIONS DO NOT INSTALL THE SAND

EXPLECO GLASS POOL SAND is supplied in two Grades

Grade 2 - (1.1-1.7mm) 70% required. **15kg Bags**

Grade 3 - (1.7-3.4 mm) 30% required. **15kg Bags**

1. Confirm filter sand weight requirements from Label on Filter.
2. Expleco Glass Pool Sand is approx 10% lighter than silica sand so you may find that you will be able to use approximately 10% less.
3. Use grade 3 – (1.7mm-3.4mm) to cover lateral tubes by approx 25mm.
4. Fill filter to required weight with remaining Grade 2 - (1.1-1.7mm.)
5. Fill Filter with water.
6. Mix 250gms of BIOGARD Filterbrite per 150kg of Expleco Glass Pool Sand, with 3 litres of hot water. Stir to dissolve and pour into filter.
7. Replace Valve assembly and turn lever to backwash. Do not start filter.
8. Leave Filter OFF for 12hrs. **Start on BACKWASH. Backwash for several minutes until sight glass is crystal clear.**
9. Run on Rinse for 30 seconds to clean and settle glass sand.
10. Turn to Filter mode and enjoy the increased efficiency and sparkle that Expleco Glass Pool Sand can deliver.

Contact 0800 777567 for Technical Assistance

Yours truly,

Tim Barnett
Marketing Manager